



GM006 - 3/4" Oval Gear Pulse Meter



The GM006 Meter is a low to medium flow range model. This meter is great for lubrication products and fluids compatible with aluminum.

ACCURACY: ± 0.5% OF READING

Select Your Body Material:

Aluminum
Stainless Steel



Features and Benefits:

- ✓ Extremely accurate even with viscous fluids.
- ✓ Handles particles sizes to 0.011"/0.28 mm.
- ✓ Meter design minimizes the number of wear-able parts – extending product life.
- ✓ Comes with Reed Switch as standard, Hall Effect Sensor* optional.
- ✓ Choose from a variety of Output and Display Options.
- ✓ Certificate of Accuracy supplied with meter.

GM006 - SPECIFICATIONS

Fitting Type:	BSP or NPT (Female)
Sensor Options:	Reed Switch or Hall Effect Sensor*
Rotor Materials:	PPS
O-Ring:	Viton (Standard), Teflon® (Optional)
Output Options:	Pulse Out or Local 4-20 mA Transmitter
Display Options:	Standard LC Display or Local 4-20 mA with Standard Display
Flow Range:	0.8 - 15.8 GPM (3 - 60 LPM)
Flow Range @ < 5 cps:	4.5 - 15.8 GPM (17 - 60 LPM)
Accuracy:	± 0.5% of reading
Repeatability:	± 0.03%
Maximum Viscosity:	Standard Rotors: 1,000 cps
Pressure Rating:	800 PSI / 55 BAR
Maximum Temperature:	
PPS Rotors:	176°F / 80°C
Typical K-Factor:	
Single Pickup:	197 PPG / 52 PPL
Double Pickup:	394 PPG / 104 PPL
Wetted Mat'l. - Housing:	
Aluminum:	Aluminum
Wetted Mat'l. - Bearings:	PPS
Wetted Mat'l. - Shaft:	316 Stainless Steel
Frequency Range:	2.6 - 51.9 Hz @ 0.8 - 15.8 GPM
Recommended Strainer Size:	60 mesh
Shipping Weight (approx.):	
Aluminum:	4.30 lbs. (1.9 kg)
Remote Display:	Option Available: Model GG500
Remote Transmitter:	Options Available: Model GA500 & GX500

* Hall Effect Sensor requires dedicated power source.

BUY SMART . BUY VALUE . BUY