



# GM001 - 1/8" Oval Gear Pulse Meter



Shown here with Standard Display

The GM001 is one of three compact meters in the Oval Gear Meter line. This meter is small and accurate. Choose from either Aluminum or 316 Stainless Steel body materials, both with stainless steel rotors. The GM001 can handle a wide range of fluid viscosities.

**ACCURACY: ± 1.0% OF READING**

### Select Your Body Material:

Aluminum

Stainless Steel

Intermediate Pressure Stainless Steel



### Features and Benefits:

- ✓ 0 - 1,000 cps viscosity.
- ✓ Compact, durable and serviceable on-site. Extremely accurate even with viscous fluids.
- ✓ Meter design minimizes the number of wear-able parts – extending product life.
- ✓ Handles particles sizes to 0.005"/0.127 mm.
- ✓ Comes with Reed Switch as standard, Hall Effect Sensor\* optional.
- ✓ Choose from a variety of Output and Display Options.
- ✓ Certificate of Accuracy supplied with meter.

### GM001 - SPECIFICATIONS

Fitting Type:	BSP or NPT (Female)
Sensor Options:	Reed Switch / Hall Effect Sensor*
Rotor Material:	316 Stainless Steel
O-Ring:	Viton (Std.), Perfluoro Elastomer (Optional)
Output Options:	Pulse Out or Local 4-20 mA Transmitter
Display Options:	Standard LC Display or Local 4-20 mA with Standard Display
Flow Range:	0.13 - 13.2 GPH (0.5 - 50 LPH)
Flow Range @ < 5 cps:	0.528 - 13.2 GPH (2 - 50 LPH)
Accuracy:	± 1.0% of reading
Repeatability:	± 0.03%
Maximum Viscosity:	1,000 cps
Pressure Rating:	
Aluminum:	75 PSI / 5 BAR
Stainless Steel:	150 PSI / 10 BAR
Intermed. Pressure SS:	800 PSI / 55 BAR
Maximum Temperature:	
Aluminum:	176°F / 80°C
Stainless Steel:	248°F / 120°C
Intermed. Pressure SS:	248°F / 120°C
Typical K-Factor:	5855.4 PPG / 1547 PPL
Wetted Mat'l. - Housing:	
Aluminum:	Aluminum
Stainless Steel:	316 Stainless Steel
Intermed. Pressure SS:	316 Stainless Steel
Wetted Mat'l. - Bearings:	Sapphire
Wetted Mat'l. - Shaft:	316 Stainless Steel
Frequency Range:	0.2 - 21.5 Hz @ 0.13 - 13.2 GPH
Recommended Strainer Size:	200 mesh
Shipping Weight (approx.):	
Aluminum:	1.0 lbs. (0.45 kg)
Stainless Steel:	2.0 lbs. (0.91 kg)
Intermed. Pressure SS:	2.0 lbs. (0.91 kg)
Remote Display:	Option Available: Model GG500
Remote Transmitter:	Options Available: Model GA500 & GX500

\* Hall Effect Sensor requires dedicated power source.

BUY SMART . BUY VALUE . BUY